

起重量 Lifting Weight		t	75/20							75/20							75/20						
跨度 Span		m	13.5	16.5	19.5	22.5	25.5	28.5	31.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5
工作级别 Working Class			A3							A5							A6						
最大起升高 度 Max. Lift Height	主 Primary	m	20							20							20						
	副 Secondary		22							22							22						
速度 Speed	起升 Lift	主 Primary	1.51							6							6.14						
		副 Secondary	6.74							9.23							9.23						
	小车运行 Handcart Travel		12.32							38.4							38.4						
	大车运行 Cart Travel		33.2			30.3				77.6			66.2				78.1			66.7			
电动机 Motor	起升 Lift	主 Primary	YZR200L-8Z/22							YZR315M-10Z/85							YZR355M-10/90						
		副 Secondary	YZR200L-8Z/22							YZR250M1-8Z/35							YZR250M1-8Z/35						
	小车运行 Handcart Travel		YZR132M2-6/5							YZR180L-8/13							YZR180L-8/13						
	大车运行 Cart Travel		YZR160L-8/11×2							YZR255M-8/26×2							YZR250M1-8/30×2						
主要尺寸 (mm) Main Size		H	331	331	331	332	331	332	332	360	360	360	361	360	361	361	360	360	360	361	361	361	361
		H1	131	131	132	132	132	133	131	131	133	132	132	132	133	132	132	132	132	132	132	133	133
		H2	398	538	542	546	844	848	850	398	538	542	546	844	848	850	400	540	544	548	846	850	852
		H3	277	291	292	292	322	322	323	277	291	292	292	322	322	323	278	292	292	292	322	323	323
		H4	158	158	158	158	158	157	157	158	158	158	158	158	157	157	158	158	158	157	158	157	157
		H0	0;50;100;150;200;250																				
重量 Weight	小车 Trolley	t	23.95							32.92							33.46						
	总重 Total Weight	t	56.3	60.2	65.2	70.9	75.8	82.4	88.4	67.2	71.1	76.1	81.9	86.7	93.3	99.4	69	73.3	78.4	84.3	89.1	96.2	101.9
最大轮压 Max. Wheel Pressure		KN	266	278	285	294	305	316	326	287	300	312	322	331	343	354	299	315	326	337	347	359	368
荐用钢轨 Recommend Steel			QU100																				

---

Track	
电源 Power Supply	三相交流 3-Phase A.C. 50Hz 380V

www.sino-lifting.com

起重量 Lifting Weight		t	80/20																							
跨度 Span		m	13	16	19	22	25	28	31	13	16	19	22	25	28	31	13	16	19	22	25	28	31			
工作级别 Working Class			A3									A5									A6					
最大起升高 度 Max. Lift Height	主 Primary	m	20									20									20					
	副 Secondary		22									22									22					
速度 Speed	起升 Lift	主 Primary	1.51									4.8									6.14					
		副 Secondary	6.74									9.23									9.23					
	小车运行 Handcart Travel	12.32									38.4									38.4						
	大车运行 Cart Travel	33.2			30.3			76.1(77.6)			65(66.2)			77.6(78.1)			66.2(66.7)									
电动机 Motor	起升 Lift	主 Primary	YZR200L-8Z/22									YZR315M-10Z/85									YZR355M-10/90					
		副 Secondary	YZR200L-8Z/22									YZR250M1-8Z/35									YZR250M1-8Z/35					
	小车运行 Handcart Travel	YZR132M2-6/5									YZR180L-8/13									YZR180L-8/13						
	大车运行 Cart Travel	YZR160L-8/11x2									YZR200M-8/18.5x2 (YZR255M-8/26x2)									YZR225M-8/22x2 (YZR250M1-8/30x2)						
主要尺寸 (mm) Main Size 注:☆H4 为单钩 ※H4 为双钩 Note: ☆H4:single hook ※H4:double hook		H	339	339	339	340	339	340	340	360	360	360	361	361	361	3616	360	360	361	361	361	361	361			
		H1	131	131	132	132	132	132	133	131	131	133	132	132	132	1330	132	132	132	132	132	132	133	133		
		H2	398	538	542	546	844	848	850	398	538	542	546	844	848	850	400	540	544	548	846	850	852			
		H3	277	291	292	292	322	322	323	277	291	292	292	322	322	3230	278	292	292	292	322	323	323			
		☆H4	167	167	166	166	166	166	166	167	167	166	166	166	166	1661	167	167	166	166	166	166	166	165		
		※H4	157	157	157	157	157	156	156	157	157	157	157	157	156	1566	157	157	157	156	157	156	156	156		
		H0	0;50;100;150;200;250																							
重量 Weigh t	小车 Trolley	t	24.6									33.8									34.4					
	总重		56.3	60.2	65.2	70.9	75.8	82.4	88.4	69.1	73.0	78.0	84.8	89.6	96.2	102.3	70.9	75.2	80.3	87.2	92.0	99.1	105			



起重量 Lifting Weight		t	100/20							
跨度 Span		m	13	16	19	22	25	28	31	
最大起升高度 Max. Lift Height	主 Primary	m	22							
	副 Secondary		22							
速度 Speed	起升 Lift	主 Primary	3.9							
		A5	4.9							
	副 Secondary	7.2								
	小车运行 Handcart Travel		33.86							
	大车运行 Cart Travel	A5	65.7							
		A6	65.7							
电动机 Motor	起升 Lift	主 Primary	YZR315M-10/85							
		A5	YZR355M-10/90							
	副 Secondary	YZR225M-8/26								
	小车运行 Handcart Travel		YZR180L-8/13							
	大车运行 Cart Travel	A5	YZR200L-8/2×18.5			YZR200L-8/2×26				
		A6	YZR225M-8/2×22			YZR225M-8/2×30				
主要尺寸 (mm) Main Size 注:☆H4 为单钩 ※H4 为双钩 Note: ☆H4:single hook ※H4:double hook		A5	H	3655	3657	3659	3665	3665	3667	3669
			H1	1330	1332	1334	1340	1340	1342	1344
			H2	538	540	544	550	850	852	854
			H3	2918	2920	2924	2930	3230	3232	3234
			☆H4	1886	1884	1882	1876	1876	1874	1872
		A6	H0	0;50;100;150;200;250						
			H	3657	3659	3661	3667	3667	3669	3671
			H1	1332	1334	1336	1342	1342	1344	1348
			H2	540	542	546	552	852	854	858
			H3	2920	2922	2926	2932	3232	3234	3238
			H4	1884	1882	1880	1874	1874	1872	1868
			HO	0、50、100、150、200、250						
重量 Weight	小车 Trolley	A5	35016							
		A6	35416							
	总重 Total Weight	A5	71563	75909	80943	88240	92898	100062	110530	
		A6	73362	77856	83005	90459	95309	103655	116110	
最大轮压 Max.Wheel Pressure		A5	337	350	364	378	389	401	412	
		A6	340	357	372	387	398	411	428	
荐用钢轨 Recommend Steel Track			QU100							
电源 Power Supply			三相交流 3-Phase A.C. 50Hz 380V							