

| | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|----------------------------|---------|-----------|-----------------------------|------|------|------|----------------|------|------|------|------------------|------|------|------|----------------|------|------|------|-------|------|--|--|--|------|--|--|--|
| 起重量 Lifting Weight | | t | 5 | | | | | | | | 10 | | | | | | | | | | | | | | | | |
| 跨度 Span | | m | 10.5 | 13.5 | 16.5 | 19.5 | 22.5 | 25.5 | 28.5 | 31.5 | 10.5 | 13.5 | 16.5 | 19.5 | 22.5 | 25.5 | 28.5 | 31.5 | | | | | | | | | |
| 最大起升高度 Max Lifting Height | | | 16 | | | | | | | | 16 | | | | | | | | | | | | | | | | |
| 工作级别 Working Class | | | A3 | | | | | | | | A3 | | | | | | | | | | | | | | | | |
| 速度 Speed | 起升 Lift | m/min | 1.95 | | | | | | | | 2.04 | | | | | | | | | | | | | | | | |
| 小车运行 Handcar Travel | | | 18.24 | | | | | | | | 18 | | | | | | | | | | | | | | | | |
| 大车运行 Cart Travel | | | 44.5 | | | | 44.9 | | | | 44.5 | | | | 44.9 | | 42.3 | | | | | | | | | | |
| 电动机 Motor | 起升 Lift | Type/kw | YZR132M1-6Z/2.5 | | | | | | | | YZR132M2-6/4 | | | | | | | | | | | | | | | | |
| 小车运行 Handcar Travel | | | YZR112M-6/1.8 | | | | | | | | YZR112M-6/1.8 | | | | | | | | | | | | | | | | |
| 大车运行 Cart Travel | | | YZR132M1-6/2.5×2 | | | | YZR132M2-6/4×2 | | | | YZR132M1-6/2.5×2 | | | | YZR132M2-6/4×2 | | | | | | | | | | | | |
| 主要尺寸 (mm) Main Size | | W | 3400 | | | | 3550 | | | | 5000 | | | | 4050 | | | | 5000 | | | | | | | | |
| | | B1 | 1140 | | | | 550 | | | | 1140 | | | | 1210 | | | | 780 | | | | | | | | |
| | | B2 | 650 | | | | 550 | | | | 650 | | | | 720 | | | | 550 | | | | | | | | |
| | | B3 | 1435 | 1485 | | | | 1535 | | | | 1635 | | | | 1460 | | | | 1510 | | | | 1585 | | | |
| | | B4 | 540 | 545 | 550 | 595 | 620 | 645 | 670 | | | | 865 | 870 | 875 | 920 | 945 | 970 | | | | | | | | | |
| | | B5 | 1256 | 1281 | 1306 | 1331 | 1356 | 1431 | 1456 | | | | 1281 | 1306 | 1331 | 1356 | 1381 | 1406 | | | | | | | | | |
| | | S1 | 800 | | | | | | | | 1050 | | | | | | | | | | | | | | | | |
| | | S2 | 1250 | | | | | | | | 1300 | | | | | | | | | | | | | | | | |
| | | F | -24 | 126 | 226 | 376 | 526 | 676 | 826 | 976 | -24 | 126 | 226 | 376 | 526 | 628 | 778 | 928 | | | | | | | | | |
| | | H | 1764 | | | | | | | | 1876 | | | | | | | | 1926 | | | | | | | | |
| | | H1 | 2526 | 2546 | 2596 | 2756 | 2906 | 3056 | 3206 | 3356 | 2526 | 2546 | 2596 | 2756 | 2906 | 3006 | 3156 | 3306 | | | | | | | | | |
| | | H2 | 735+H0 | | | | | | | | 735+H0 | | | | | | | | | | | | | | | | |
| | | H3 | 31 | | | | | | | | 561.5 | | | | | | | | 511.5 | | | | | | | | |
| | | 重量 Weight | 小车 Handcart | | 2.4 | | | | | | | | 3.4 | | | | | | | | | | | | | | |
| 总重量 Total Weight | 开式 Open | | t | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 闭式 Close | 12.4 | 14.1 | 15.8 | 18.6 | 21 | 25.4 | 28.6 | 31.5 | 13.8 | 15.4 | 18.1 | 19.9 | 22.5 | 27 | 30.3 | 33.3 | | | | | | | | | |
| | | | 12.8 | 14.5 | 16.2 | 18.9 | 21.4 | 25.8 | 28.9 | 31.8 | 14.1 | 15.8 | 18.5 | 20.3 | 22.9 | 27.3 | 30.6 | 33.7 | | | | | | | | | |
| 最大轮压 Max. Wheel Pressure | | kN | 85 | 90 | 96 | 103 | 110 | 121 | 129 | 136 | 108 | 114 | 122 | 128 | 135 | 149 | 157 | 165 | | | | | | | | | |
| 荐用钢轨 Recommend Steel Track | | | 38 | | | | | | | | 43 | | | | | | | | | | | | | | | | |
| 电源 Power Supply | | | 三相交流 3-Phase A.C. 50Hz 380V | | | | | | | | | | | | | | | | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | | | | | | |
|----------------------------|---------------------|---------------------|----------------------------|------|------|------|--------|------|------|------|----------------|------|------|------|--------|------|------|------|------|------|------|------|------|------|------|
| 起重量 Lifting Weight | | t | 16/3.2 | | | | | | | | 20/5 | | | | | | | | | | | | | | |
| 跨度 Span | | | 10.5 | 13.5 | 16.5 | 19.5 | 22.5 | 25.5 | 28.5 | 31.5 | 10.5 | 13.5 | 16.5 | 19.5 | 22.5 | 25.5 | 28.5 | 31.5 | | | | | | | |
| 最大起升高度 (m) | 主 Primary | m | 16 | | | | | | | | 12 | | | | | | | | | | | | | | |
| Max Lifting Height | 副 Secondary | | 24 | | | | | | | | 18 | | | | | | | | | | | | | | |
| 工作级别 Working Class | | | A3 | | | | | | | | A3 | | | | | | | | | | | | | | |
| 速度 Speed | 起升 Lift | 主 Primary | 2.23 | | | | | | | | 2.31 | | | | | | | | | | | | | | |
| | | 副 Secondary | 9.2 | | | | | | | | 9.28 | | | | | | | | | | | | | | |
| | 小车运行 Handcar Travel | | 18 | | | | | | | | 18 | | | | | | | | | | | | | | |
| | 大车运行 Cart Travel | | 42.8 | | | | 40.8 | | | | 42.3 | | | | 40.8 | | | | | | | | | | |
| 电动机 Motor | 起升 Lift | 主 Primary | YZR160M2-6/8.5 | | | | | | | | YZR160M2-6/8.5 | | | | | | | | | | | | | | |
| | | 副 Secondary | YZR160M2-6/8.5 | | | | | | | | YZR160L-8/9 | | | | | | | | | | | | | | |
| | | 小车运行 Handcar Travel | YZR112M-6/1.8 | | | | | | | | YZR112M-6/1.8 | | | | | | | | | | | | | | |
| | | 大车运行 Cart Travel | YZR132M2-6/4×2 | | | | | | | | YZR132M2-6/4×2 | | | | | | | | | | | | | | |
| 主要尺寸 (mm) Main Size | | B _Q | 4000 | | | 4100 | | | 5000 | | | 4500 | | | 4600 | | | 5500 | | | | | | | |
| | | B ₁ | 1190 | | | | 780 | | | | 1190 | | | | 780 | | | | | | | | | | |
| | | B ₂ | 765 | | | | 610 | | | | 765 | | | | 610 | | | | | | | | | | |
| | | B ₃ | 1560 | | | | 1635 | | | | 1560 | | | | 1635 | | | | | | | | | | |
| | | B ₄ | 870 | 895 | 920 | 945 | 970 | 1120 | 1145 | 1170 | 1195 | 1220 | 1356 | 1381 | 1406 | 1431 | 1456 | 1356 | 1381 | 1406 | 1431 | 1456 | | | |
| | | B ₅ | 1356 | 1381 | 1406 | 1431 | 1456 | 1356 | 1381 | 1406 | 1431 | 1456 | 1356 | 1381 | 1406 | 1431 | 1456 | 1356 | 1381 | 1406 | 1431 | 1456 | | | |
| | | S ₁ | 1040 | | | | | | | | 1040 | | | | | | | | | | | | | | |
| | | S ₂ | 1850 | | | | | | | | 1900 | | | | | | | | | | | | | | |
| | | S ₃ | 1500 | | | | | | | | 1450 | | | | | | | | | | | | | | |
| | | S ₄ | 2310 | | | | | | | | 2310 | | | | | | | | | | | | | | |
| | | b | 230 | | | | 260 | | | | 230 | | | | 260 | | | | | | | | | | |
| | | F | 80 | 180 | 240 | 388 | 538 | 688 | 838 | 80 | 82 | 182 | 242 | 390 | 540 | 690 | 840 | 80 | 82 | 182 | 242 | 390 | 540 | 690 | 840 |
| | | H | 2095 | | | | 2185 | | | | 2094 | | | | 2184 | | | | | | | | | | |
| | | H ₁ | 2520 | 2550 | 2620 | 2768 | 2918 | 3068 | 3218 | 2520 | 2522 | 2552 | 2622 | 2770 | 2920 | 3070 | 3220 | 2520 | 2522 | 2552 | 2622 | 2770 | 2920 | 3070 | 3220 |
| | | H ₂ | 785+Ho | | | | 880+Ho | | | | 785+Ho | | | | 880+Ho | | | | | | | | | | |
| | | H ₃ | 654 | | | | 564 | | | | 554 | | | | 464 | | | | | | | | | | |
| H ₄ | 725 | | | | | | | | 412 | | | | | | | | | | | | | | | | |
| 重量 Weight | 小车 Handcart | | 5.8 | | | | | | | | 6.9 | | | | | | | | | | | | | | |
| | 总重量 Total Weight | 开式 Open | 17.7 | 19.2 | 21.2 | 25.5 | 28.0 | 32.3 | 35.6 | 38.7 | 19.1 | 20.7 | 22.9 | 27.4 | 30.0 | 34.5 | 38.2 | 41.4 | | | | | | | |
| | | 闭式 Close | 18.1 | 19.6 | 21.6 | 26.0 | 28.4 | 32.7 | 36.0 | 37.8 | 19.4 | 21.1 | 23.3 | 27.8 | 30.4 | 34.9 | 38.5 | 41.8 | | | | | | | |
| 最大轮压 Max. Wheel Pressure | | kN | 146 | 154 | 162 | 183 | 192 | 203 | 212 | 222 | 151 | 162 | 167 | 182 | 190 | 202 | 212 | 221 | | | | | | | |
| 荐用钢轨 Recommend Steel Track | | | 43kg/m QU70 | | | | | | | | 43kg/m QU70 | | | | | | | | | | | | | | |
| 电源 Power Supply | | | 三相交流 3-Phase A.C.50Hz 380V | | | | | | | | | | | | | | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | |
|----------------------------|---------------------|-------------|-----------------------------|------|------|------------------|------|-------|------|----------------------|------|------------------|------|------|------|------|------|------|
| 起重量 Lifting Weight | | t | 32/5 | | | | | | | 50/10 | | | | | | | | |
| 跨度 Span | | | 10.5 | 13.5 | 16.5 | 19.5 | 22.5 | 25.5 | 28.5 | 31.5 | 10.5 | 13.5 | 16.5 | 19.5 | 22.5 | 25.5 | 28.5 | 31.5 |
| 最大起升高度 (m) | 主 Primary | m | 16 | | | | | | | 12 | | | | | | | | |
| Max Lifting Height | 副 Secondary | | 18 | | | | | | | 16 | | | | | | | | |
| 工作级别 Working Class | | | A3 | | | | | | | A3 | | | | | | | | |
| 速度 Speed | 起升 Lift | 主 Primary | 1.97 | | | | | | | 1.75 | | | | | | | | |
| | | 副 Secondary | 9.28 | | | | | | | 6.04 | | | | | | | | |
| | 小车运行 Handcar Travel | n | 19 | | | | | | | 18.24 | | | | | | | | |
| | 小车运行 Handcar Travel | | 40.8 | | | 47.7 | | | | 47.7 | | | 48.1 | | | | | |
| 电动机 Motor | 起升 Lift | 主 Primary | YZR160L-6Z/13 | | | | | | | YZR200L-8Z/18.5 | | | | | | | | |
| | | 副 Secondary | YZR160L-8Z/9 | | | | | | | YZR180L-8Z/13 | | | | | | | | |
| | 小车运行 Handcar Travel | Type/ kw | YZR132M1-6/2.5 | | | | | | | YZR132M2-6/4 | | | | | | | | |
| | 小车运行 Handcar Travel | | YZR132M2-6/4× 2 | | | YZR160M1-6/6.3×2 | | | | YZR160M1-6/6.3× 2 | | YZR160M2-6/8.5×2 | | | | | | |
| | 小车运行 Handcar Travel | | YZR132M2-6/4× 2 | | | YZR160M1-6/6.3×2 | | | | YZR160M1-6/6.3× 2 | | YZR160M2-6/8.5×2 | | | | | | |
| 主要尺寸 (mm) Main Size | | W | 4650 | | 4700 | | 5000 | | | 4800 | | | 5500 | | | | | |
| | | B1 | 1225 | | | | | | | 1275 | | | | | | | | |
| | | B2 | 765 | | | | | | | 700 | | | | | | | | |
| | | B3 | 1660 | | | | | | | 1660 | | | | | | | | |
| | | B4 | 1205 | 1230 | 1255 | 1380 | 1405 | 1325 | 1305 | 1330 | 1355 | 1380 | 1405 | | | | | |
| | | B5 | 1381 | 1406 | 1431 | 1456 | 1481 | 1381 | 1406 | 1431 | 1456 | 1481 | | | | | | |
| | | S1 | 1070 | | | | | | | 1005 | | | | | | | | |
| | | S2 | 2050 | | | | | | | 2200 | | | | | | | | |
| | | S3 | 1700 | | | | | | | 2000 | | | | | | | | |
| | | S4 | 2680 | | | | | | | 3195 | | | | | | | | |
| | | b | 260 | | | 300 | | | | 300 | | | | | | | | |
| | | F | 90 | 94 | 244 | 264 | 414 | 564 | 714 | 814 | -79 | 96 | 102 | 252 | 402 | 552 | 702 | 802 |
| | | H | 2437 | 2439 | 2569 | | | | | 2981 | | | 2987 | | | | | |
| | | H1 | 2520 | 2524 | 2614 | 264 | 279 | 294 | 309 | 3194 | 2531 | 2526 | 2532 | 263 | 278 | 293 | 308 | 3182 |
| | | | | | | 4 | 4 | 4 | 4 | | | | | 2 | 2 | 2 | 2 | |
| | | H2 | 880+Ho | | | 1010+Ho | | | | 1030+Ho | | | | | | | | |
| H3 | 603 | 601 | 471 | | | | | 950 | | 944 | | | | | | | | |
| H4 | 730 | | | | | | | 918.5 | | | | | | | | | | |
| 重量 Weight | 小车 Handcart | t | 10.0 | | | | | | | 14.5 | | | | | | | | |
| | 总重量 Total Weight | 开式 Open | 24.9 | 27.7 | 30.7 | 35.3 | 38.7 | 43.7 | 47.4 | 51.4 | 33.9 | 37.0 | 41.3 | 45.3 | 49.3 | 54.8 | 58.8 | 64.1 |
| | 总重量 Total Weight | 闭式 Close | 25.3 | 28.1 | 31.1 | 35.7 | 39.1 | 44.1 | 47.8 | 51.8 | 34.2 | 37.4 | 41.6 | 45.7 | 49.7 | 55.2 | 59.2 | 64.5 |
| 最大轮压 Max. Wheel Pressure | | kN | 244 | 260 | 274 | 297 | 309 | 320 | 340 | 350 | 373 | 396 | 417 | 432 | 453 | 471 | 484 | 500 |
| 荐用钢轨 Recommend Steel Track | | | QU70 □90×90 | | | | | | | QU70 | | | | | | | | |
| 电源 Power Supply | | | 三相交流 3-Phase A.C. 50Hz 380V | | | | | | | | | | | | | | | |