

起重量 Lifting Weight		t	5							10								
跨度 Span		m	10.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5	10.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5
最大起升高度 Max Lifting Height			16							16								
工作级别 Working Class		A3																
速度 Speed	起升 Lift	m/min	0.2~1.95							0.2~2.04								
	小车运行 Handcar Travel		2~18.24							1.8~18								
	大车运行 Cart Travel		4.5~44.5				4.5~44.9			4.5~44.5			4.5~44.9		4.5~42.3			
电动机总功率 Motor Total Power		kw	9.3				12.3			10.8			13.8					
主要尺寸 (mm) Main Size		BQ	3400			3550		5000			4050			5000				
		B1	1140				550			1140		1210		780				
		B2	650				550			650		720		550				
		B3	1435	1485	1535	1635			1460	1510		1585						
		B4	540	545	550	595	620	645	670	865	870	875	920	945	970			
		B5	1256	1281	1306	1331	1356	1431	1456	1281	1306	1331	1356	1381	1406			
		S1	800							1050								
		S2	1250							1300								
		F	-24	126	226	376	526	676	826	976	-24	126	226	376	526	628	778	928
		H	1764							1876					1926			
		H1	2526	2546	2596	2756	2906	3056	3206	3356	2526	2546	2596	2756	2906	300	315	330
		H2	735+H0							735+H0								
		H3	31							561.5					511.5			
重量 Weight	小车 Handcart		t	2.4							3.4							
	总重量 Total Weight	开式 Open		13.5	14.7	16.6	19.3	21.9	27	30.2	33.3	14.8	16.5	19.4	21.6	24.5	29.3	32.8
		闭式 Close	13.9	15.1	17	19.6	22.9	27.4	30.6	33.7	15.1	16.9	19.8	21.8	24.9	29.7	33.1	36.4
最大轮压 Max. Wheel Pressure		kN	85	90	96	103	110	121	129	136	108	114	122	128	135	149	157	165
荐用钢材 Recommend Steel Track		38kg/m							43kg/m									
电源 Power Supply		三相交流 3-Phase A.C 50Hz 380V																

起重量 Lifting Weight		t	16/3.2								20/5																			
跨度 Span		m	10.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5	10.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5												
最大起升高度 Max Lifting Height	主 Primary	m	16								12																			
	副 Secondary		18								14																			
工作级别 Working Class		A3																												
速度 Speed	起升 Lift	主 Primary	0.5~2.23								0.5~2.0																			
		副 Secondary	0.95~9.2								0.95~9.28																			
	小车运行 Handcar Travel		m/min	1.8~18								1.8~18																		
	大车运行 Cart Travel			4.5~42.8				4.2~40.8				4.5~42.3				4.2~40.8														
电动机总功率 Motor Total Power		kw	24.6								27.8																			
主要尺寸 (mm) Main Size		BQ	4000				4100				5000				4500				4600				5500							
		B1	1190								780								1190								780			
		B2	765								610								765								610			
		B3	1560				1635				1560				1635															
		B4	870	895	920	945	970	1120	1145	1170	1195	1220	1120	1145	1170	1195	1220	1120	1145	1170	1195	1220								
		B5	1356	1381	1406	1431	1456	1356	1381	1406	1431	1456	1356	1381	1406	1431	1456	1356	1381	1406	1431	1456								
		S1	1040								1040																			
		S2	1850								1900																			
		S3	1500								1450																			
		S4	2310								2310																			
		b	230				260				230				260															
		F	80	180	240	388	538	688	838	80	82	182	242	390	540	690	840	80	82	182	242	390	540	690	840					
		H	2095				2185				2094				2184															
		H1	2520	2550	2620	2768	2918	3068	3218	2520	2550	2620	2768	2918	3068	3218	2520	2550	2620	2768	2918	3068	3218							
		H2	735+H0				880+H0				785+H0				880+H0															
		H3	654				564				554				464															
H4	725								412																					
重量 Weight	小车 Handcart		t	6.33								6.9																		
	总重量 Total Weight	开式 Open		20.2	22.4	24.8	29	31.8	35.9	39.7	43.1	21.2	23.8	26.3	30.8	33.8	38.3	42.2	46											
		闭式 Close		20.6	22.8	25.2	29.4	32.2	36.3	40.1	42.1	21.5	24.2	26.7	31.2	34.2	38.7	42.5	46.4											
最大轮压 Max. Wheel Pressure		kN	146	154	162	183	192	203	212	222	151	162	167	182	190	202	212	221												
荐用钢材 Recommend Steel Track		43kg/m QU70								43kg/m QU70																				
电源 Power Supply		三相交流 3-Phase A.C 50Hz 380V																												

起重量 Lifting Weight		t	32/5								50/10													
跨度 Span		m	10.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5	10.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5						
最大起升高度	主 Primary	m	16								12													
Max Lifting Height	副 Secondary		18								16													
工作级别 Working Class		A3																						
速度 Speed	起升 Lift	主 Primary	0.2~1.97								0.2~1.75													
		副 Secondary	0.95~9.28								0.62~6.04													
	小车运行 Handcar Travel		m/min	1.9~19								1.9~18.24												
	大车运行 Cart Travel			4.2~40.8				4.8~47.7				4.8~47.7				5~48.1								
电动机总功率 Motor Total Power		kw	32.5				37.1				48.1				52.5									
主要尺寸 (mm) Main Size		BQ	4650				4700				5000				4800				5000					
		B1	1225								1275													
		B2	765								700													
		B3	1660								1660													
		B4	1205	1230	1255	1380	1405	1325	1305	1330	1355	1380	1405	1205	1230	1255	1380	1405	1325	1305	1330	1355	1380	1405
		B5	1381	1406	1431	1456	1481	1381	1406	1431	1456	1481	1381	1406	1431	1456	1481							
		S1	1070								1040													
		S2	2050								2200													
		S3	1700								2000													
		S4	2680								3195													
		b	260				300				300													
		F	90	94	244	264	414	564	714	814	-79	96	102	252	402	552	702	802						
		H	2437	2439	2569						2981				2987									
		H1	2520	2524	2614	264	279	294	309	319	253	252	2532	263	278	293	308	3182						
		H2	880+H0				1010+H0				1030+H0													
		H3	603	601	471						950				944									
		H4	730								918.5													
重量 Weight	小车 Handcart		10.9								15.5													
	总重量 Total Weight	开式 Open	27.6	31.1	34.1	39.3	42.9	48.3	51.3	56.5	39.4	42.9	47.6	51.9	55.9	61.8	66	71.2						
		闭式 Close	27.9	31.5	34.5	39.7	43.3	48.7	51.7	56.9	39.7	43.3	47.9	52.3	56.3	62.2	66.4	71.6						
最大轮压 Max. Wheel Pressure		kN	244	260	274	297	309	327	340	350	373	396	417	432	453	471	484	500						
荐用钢材 Recommend Steel Track		QU70 □90×90								QU70														
电源 Power Supply		三相交流 3-Phase A.C 50Hz 380V																						

起重量 Lifting Weight		t	75/20							80/20							
跨度 Span		m	13.5	16.5	19.5	22.5	25.5	28.5	31.5	13	16	19	22	25	28	31	
工作级别 Working Class			A3														
起升高度(m) Max Lifting Height	主 Primary		20							20							
	副 Secondary		22							22							
速度 Speed	起升 Lift	主 Primary	0.19~1.66							0.19~1.66							
		副 Secondary	0.7~6.74							0.7~6.74							
	小车运行 Handcar Travel		m/min	1.3~12.32							1.3~12.32						
	大车运行 Cart Travel			3.5~33.2				3.2~30.3			3.5~33.2				3.2~30.3		
电动机总功率 Motor Total Power		kw	71							71							
主要尺寸 (mm) Main Size		H	3252	3252	3256	3260	3258	3262	3264	3392	3392	3396	3400	3398	3402	3404	
		H1	1318	1318	1332	1326	1324	1328	1330	1318	1318	1322	1326	1324	1328	1330	
		H2	398	538	542	546	844	848	850	398	538	542	546	844	848	850	
		H3	2778	2918	2922	2926	3224	3228	3230	2778	2918	2922	2926	3224	3228	3230	
		☆H4	1588	1588	1584	1580	1582	1578	1576	1673	1673	1669	1665	1667	1663	1661	
		※H4								1578	1578	1574	1570	1572	1568	1566	
		H0	0,50,100,150,200,250														
重量 Weight	小车 Handcart	t	24.0							28.6							
	总重量 Total Weight		60	65	71.7	76.8	83	88	98.1	65	70	74.9	81.8	88.7	93.5	99.8	
最大轮压 Max. Wheel Pressure		kN	266	276	285	294	305	316	326	294	307	319	329	338	350	361	
荐用钢材 Recommend Steel Track		QU100															
电源 Power Supply		三相交流 3-Phase A.C 50Hz 380V															

起重量 Lifting Weight		t	100/20						
跨度 Span		m	13	16	19	22	25	28	31
工作级别 Working Class			A5						
最大起升高度(m) Max Lifting Height	主 Primary	m	22						
	副 Secondary		22						
速度 Speed	起升 Lift	主 Primary	0.19~1.66						
		副 Secondary	0.72~6.74						
	小车运行 Handcar Travel		m/min	1.3~12.32					
	大车运行 Cart Travel			3.5~33.2			3.2~30.3		
总功率 Total Power		kw	161			176			
主要尺寸 (mm) Main Size		H	3360	3362	3364	3370	3370	3372	3374
		H1	1330	1332	1334	1340	1340	1342	1344
		H2	538	540	544	550	850	852	854
		H3	2918	2920	2924	2930	3230	3232	3234
		H4	1886	1884	1882	1876	1876	1874	1872
		H0	0,50,100,150,200,250						
重量 Weight	小车 Handcart	t	32.4						
	总重量 Total Weight		71.3	76	81.7	88.2	93.9	101.4	109
最大轮压 Max. Wheel Pressure		kN	337	350	364	378	389	401	412
荐用钢轨 Recommend Steel Track			QU120						
电源 Power Supply			三相交流 3-Phase A.C 50Hz 380V						