

起重量 Lifting Weight		t	5								10										
跨度 Span		m	10.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5	10.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5			
最高起升高度 Max. Lifting Height			16								16										
工作级别 Working Class			A5								A5										
速度 Speed	起升 Lift	m/min	3.7								3.3										
	小车运行 Handcar Travel		9.3								10.3										
	大车运行 Cart Travel		12								24				12.5						
电动机总功率 Motor Total Power		kw	9.3				12.3				10.8				13.8						
主要尺寸 (mm) Main Size		BQ	3400			3550			5000			4050			5000						
		B1	1140(500)				550(500)				1140(500)			1210(570)		780(500)					
		B2	650				550				650			720		550					
		B3	1535	1585	1485	1535			1635			1560	1610	1510	1585						
		B4	540	545	550	595	620	645	670			865	870	875	920	945	970				
		B5	1356	1381	1306	1331	1356	1431	1456			1381	1406	1331	1356	1381	1406				
		S1	900								1050										
		S2	1250								1300										
		F	-24	126	226	376	526	676	826	976	-24	126	226	376	526	628	778	928			
		H	1764								2756								1926		
		H1	2526	2546	2596	2756	2906	3056	3206	3356	2526	2546	2596	2756	2906	300	315	330			
		H2	735+H0								735+H0								785+H0		
		H3	31								561.5								511.5		
重量 Weight	小车 Handcart		t	1.8								3.42									
	总重量 Total Weight	开式 Open		11.8	13.6	15.3	18.1	20.5	24.9	28	31	14	15.7	18.4	20.2	22.9	27.4	30.7	33.8		
		闭式 Close		12.2	14	15.7	18.5	20.9	25.3	28.4	31.4	14.4	16.1	18.8	20.6	23.2	27.8	31.1	34.2		
	地面 Ground	10.9		12.8	14.4	17.2	19.1	23.9	27.1	30.1	13.5	14.9	17.5	19.2	21.9	26.3	29.2	32.3			
最大轮压 Max. Wheel Pressure		kN	79	84	90	96	103	115	123	130	107	113	121	127	134	148	156	163			
荐用钢材 Recommend Steel track			38kg/m								43kg/m										
电源 Power Supply			三相交流 3-Phase A.C 50Hz 380V																		

起重量 Lifting Weight		t	16/3.2								20/5								
跨度 Span			10.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5	10.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5	
最大起升高度	主 副	m	16								12								
Max. Lifting Height			18								14								
工作级别 Working Class			A5								A5								
速度 Speed	主起升 main Lift	m/min	3.6								2.7								
	副起升 aux lift		3.8								3.7								
	小车运行 Handcar Travel		10.3								10.3								
	大车运行 Cart Travel		12.5				12.6				12.5				12.6				
主要尺寸 (mm) Main Size		BQ	5940		5944		6434		5940		5944		6434						
		B	4000		4100		5000		4000		4100		5000						
		B1	1230		1182		817		1230		1182		817						
		B2	710		662		617		710		662		617						
		S1	1040								1030								
		S2	1850								1900								
		S3	2310								2320								
		S4	1500								1450								
		b	230		260		230		260										
		k	2000								2000								
		BX	2400								2400								
		H	2095		2185		2097												
		H1	850		940		850												
		H2	80	180	240	388	538	68	838	80	82	182	242	390	540	690	840		
		H3	2520	2550	2620	276 3	2918	306 8	3218	2520	2522	255 2	262 2	277 0	2920	3070	322 0		
		H4	729		639		701		611										
H5	770								496										
h	820																		
重量 Weight		小车 Handcart		6.22								6.85							
总重量 Total Weight	空操 地操	t	19.1	20.3	23.4	26.4	28.8	33.1	36.3	39.4	19.9	21.3	23.5	27.7	30.3	34.6	38.3	41.5	
			17.7	18.9	22	25	27.4	31.7	34.9	38	18.5	19.9	22.1	26.3	28.9	33.2	36.9	40.1	
最大轮压 Max. Wheel Pressure		kN	144	152	160	180	189	198	210	217	163	173	182	204	213	224	235	247	
荐用钢轨 Recommend Steel track		43kg/m/QU70																	
电源 Power Supply		三相交流 3-Phase A.C 50Hz 380V																	

起重量 Lifting Weight		t	32/5								50/10							
跨度 Span			10.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5	10.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5
最大起升高度	主	m	16								12							
Max. Lifting Height	副		18								14							
工作级别 Working Class			A5								A5							
速度 Speed	主起升 main Lift	m/min	2.6								1.9							
	副起升 aux lift		3.62								3.37							
	小车运行 Handcar Travel		9.63								8.83							
	大车运行 Cart Travel		13.8	14.2							14.2							
主要尺寸 (mm) Main Size	BQ	647	6620				6924				6724				2824		7144	
	B	4650	4700				5000				4800				5000			
	B1	1212	1260				1262				1262				1312		1362	
	B2	612	660				662				662				712		782	
	S1	1070								1005								
	S2	2050								2200								
	S3	2680								3195								
	S4	1700								2000								
	b	260				300				300								
	k	2500								2500								
	BX	2800								3580								
	H	2343	2345			2475				2726				2732				
	H1	940+HO				1035+HO				1070+HO				1090+HO				
	H2	90	94	244	264	414	564	714	814	-79	96	102	252	402	552	702	802	
	H3	2520	2524	2614	2644	279 4	3944	309 4	3194	2531	2526	253 2	263 2	278 2	2932	3082	318 2	
	H4	705	701			571				1020				1040				
	H5	790								948								
h	820								675									
重量 Weight	小车 Handcart	10.87								15.42								
	总重量 Total Weight	t	27	30	33	30	41	46	50	54	37	40	44	49	53	50	62	68
最大轮压 Max. Wheel Pressure		kN	237	250	262	275	289	305	317	327	333	354	373	385	404	421	434	450
荐用钢轨 Recommend Steel track			QU70 或方钢 90								QU80 或方钢 100							
电源 Power Supply			三相交流 3-Phase A.C 50Hz 380V															