

起重量 Lifting Weight		t	5								10															
跨度 Span			10.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5	10.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5								
起升高度 Max Lift Height		m	16																							
工作级别 Working Class			A6 重级 Heavy								A6 重级 Heavy															
速度 Speed	起升 Lift	m/min	15.6								10.4															
	小车运行 Handcart Travel		37.2								43.8															
	大车运行 Cart Travel		115.6				116.8				115.6				116.8				112.5							
电动机 Motor	起升 Lift	type/kw	YZR180L-6/15								YZR200L-6/22															
	小车运行 Handcart Travel		YZR132M-6/2.5								YZR132M1-6/2.5															
	大车运行 Cart Travel		YZR160M2-6/5.5x2				YZR160M2-6/7.5x2				YZR160M2-6/5.5x2				YZR160M2-6/7.5x2											
主要尺寸 (mm) Main Size		H	1764								1874				1926											
		H1	252	254	259	275	290	3056	3206	3356	2526	2546	2596	275	290	300	315	330								
		H2	765+H0				800+H0				800+H0				850+H0											
		H3	761.5								1282				1232											
		h	870																							
		Lx	1400±2								2000															
		B	5190				5340				6100				5840				5980				6330			
		BQ	3400				3550				5000				4050				5000							
		BX	1100								1400															
		b	230																							
		F	-24	126	226	376	526	676	826	976	-24	126	226	376	526	676	826	976								
		S1	800								1050															
		S2	1250								1300															
重量 Weight	小车运行 Handcart Travel	t	2.329								3.651															
	总重 Total Weight		14	15	17	20	22	27	31	34	15	17	20	22	25	30	33	36								
最大轮压 Max. Wheel Pressure		t	8.5	9.1	9.2	10.4	11.1	12.5	13.3	13.8	11.1	11.8	12.6	13.1	13.8	15.4	16.3	17.1								
荐用钢轨 Recommend Steel Track			38kg/m								43kg/m															
电源 Power Supply			三相交流 3-Phase A.C. 50Hz 380V																							

起重量 Lifting Weight		t	16/3.2								20/5							
跨度 Span			10.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5	10.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5
最大起升高度 Max Lift Height	主 Primary	m	16								12							
	副 Secondary		18								14							
工作级别 Working Class			A6 重级 Heavy								A 重级 Heavy							
速度 Speed	起升 Lift	主 Primary	13								12.3							
		副 Secondary	19.7								19.5							
	小车运行 Handcart Travel		44.6															
	大车运行 Cart Travel		112.5				101.4				112.5				101.4			
电动机 Motor	起升 Lift	主 Primary	YZR250M1-6/37								YZR250M2-6/45							
		副 Secondary	YZR160L-6/13								YZR180L-6/17							
	小车运行 Handcart Travel		YZR132M2-6/4															
	大车运行 Cart Travel		YZR160M2-6/7.5x 2				YZR160L-6/11x2				YZR160M2-6/7.5x 2				YZR160L-6/11x2			
主要尺寸 (mm) Main Size		H	2095	2097	2187	2185	2097	2099	2189									
		H1	2570	2550	2620	2770	2920	3070	3220	2570	2574	2554	2624	2772	2922	3072	3222	
		H2	850+H0				940+H0				850+H0				940+H0			
		H3	1527	1525	1435	1437				1461	1459	1369						
		H4	1000								596							
		h									820							
		Lx	2000															
		B	6235				6835				6235				6835			
		BQ	4400				5000				4400				5000			
		Bx	6235															
		b	230				260				230				260			
		F	80	180	240	390	540	690	840	80	84	184	244	392	542	692	842	
		S1	1040								1030							
		S2	1850								1900							
		S3	1500								1450							
		S4	2310								2320							
重量 Weight	小车运行 Handcart Travel	t	6.592								8.64							
	总重 Total Weight		21	23	25	29	32	36	40	44	22	24	27	31	34	39	43	46
最大轮压 Max. Wheel Pressure		t	15.5	16.4	17.3	19.4	20.3	21.4	22.3	23.2	17.7	18.8	19.9	22.1	23.3	24.3	25.5	26.5
荐用钢轨 Recommend Steel Track			43kg/m QU70															
电源 Power Supply			三相交流 3-Phase A.C. 50Hz 380V															